10GEPON OLT PR30 XFP Transceiver

XFP Series



- IEEE 802.3av D3.4 compliant
- IEEE 802.3ah™-2004 compliant
- Bi-directional XFP transceiver
- Pluggable 10 Gbps XFP MSA compliant footprint
- XFP package with SC/UPC receptacle optical interface
- Single +3.3 V power supply
- Extended operating temperature range of -40 °C to 85 °C
- Metal enclosure for durability and low EMI
- Low jitter provides high transmission performance

The ACT 10G-EPON OLT XFP transceiver is a hot-pluggable, single-fiber bidirectional optical module designed for use in EPON OLT equipment. It supports the optical interface between the OLT and multiple ONUs in fiber-to-the-home (FTTH), fiber-to-the-building (FTTB), and other broadband access network applications.


The module supports 10.3125 Gbps symmetric, 10.3125 Gbps downstream/1.25 Gbps upstream asymmetric,2.50 Gbps downstream/1.25 Gbps upstream asymmetric, and legacy 1.25 Gbps symmetric operation, enabling the OLT to serve both 10G-EPON and 1G-EPON networks. It integrates high-power 1577 nm EML and 1490 nm DFB transmitters with high-sensitivity 1270 nm and 1310 nm burst-mode APD receivers. utilizing a single fiber with a standard SC/UPC connector.

Housed in an XFP form factor with an SC receptacle, the module supports transmission distances of up to 20 km over single-mode fiber. It also provides digital diagnostic monitoring, hot-pluggable operation, low EMI, robust ESD protection, and 3.3 V/5 V power supplies. Commercial- and industrial-temperature versions are available, and the module is RoHS compliant.


Key Features

- TX 10.3125 Gbps / burst-mode RX 10.3125 Gbps on single fiber
- TX 10.3125 Gbps / burst-mode RX 1.25 Gbps on single fiber
- TX 1.25 Gbps / burst-mode RX 1.25 Gbps on single fiber
- 1577 nm electro-absorption-modulated laser (EML) transmitter
- 1490 nm distributed-feedback (DFB) laser diode
- 1270 nm and 1310 nm avalanche photodiode (APD) receiver
- Support 20 km transmission distance over single-mode fiber (SMF)
- Low EMI and ESD protection
- Digital diagnostic monitor interface
- RoHS compliance


Outline Diagram



Recommended Circuit Schematic



EEPROM Information



Pin Descriptions

Pin No.	Name	Description	Notes
1	GND	Module Ground	
2	TX_1G_Pa	Non-Inverted Transmit Data in	LVPECL input, AC coupled
3	TX_1G_Na	Inverted Transmit Data in	LVPECL input, AC coupled
4	GND	Module Ground	
5	TX_DIS	Transmitter Disable	LVTTL Input, Low: transmitter on
6	VCC5	+5V Power Supply	
7	GND	Module Ground	
8	VCC3_TX	Transmitter 3.3V Power Supply	
9	VCC3_RX	Receiver 3.3V Power Supply	
10	SCL	The clock line	The clock line of two wire serial interface
11	SDA	The data line	The data line of two wire serial interface
12	MOD_ABS	Indicates Module is not present.	Grounded in the Module
13	N.C.	No connect in the transceiver	
14	RX_LOS	Loss of signal	LVTTL output, RX LOS pin indication 10G receiver or 1.25G receiver LOS status.
15	GND	Module Ground	
16	GND	Module Ground	
17	RD_10G_N	Inverted 10G Received Data Out	CML
18	RD_10G_P	Non-inverted 10G Received Data Out	CML
19	GND	Module Ground	
20	RD_1G_N	Inverted 1G Received Data Out	LVPECL Output, DC coupled
21	RD_1G_P	Non-inverted 1G Received Data Out	LVPECL Output, DC coupled
22	N.C.	No connect in the transceiver	
23	RSSI_TRIG	RSSI Trigger for Transceiver	High: enable RSSI A/D conversion
24	N.C.	No connect in the transceiver	
25	N.C.	No-connect in the transceiver	
26	N.C.	No-connect in the transceiver	
27	GND	Module Ground	
28	TX_10G_N	Inverted Transmit Data in	CML input, AC coupled

29	TX_10G_P	Non-Inverted Transmit Data in	CML input, AC coupled
30	GND	Module Ground	

Specifications

Absolute Maximum Ratings					
Parameter	**Symbol**	**Min**	**Max**	**Units**	**Notes**
Storage Ambient Temperature	T_{STG}	-40	85	°C	
Commercial Case Operating Temperature Range	T_C	0	70	°C	
Industrial Case Operating Temperature Range		-40	85	°C	
Operating Humidity	OH	5	95	%	

Recommended Operating Condition						
Parameter	**Symbol**	**Min**	**Typ**	**Max**	**Unit**	**Notes**
VCC3 Power Supply Voltage	V_{CC}	3.13	3.3	3.47	V	
VCC5 Power Supply Voltage	V_{CC}	4.75	5	5.25	V	
VCC3 Power Supply Current	ICC3		-	900	mA	
VCC5 Power Supply Current	ICC5		-	300	mA	
Line Rate			10.3125/1.25		Gbps	
Data Rate Drift		-100		+100	ppm	

10G EPON Transmitter Optical Characteristics						
Parameter	**Symbol**	**Min.**	**Typ.**	**Max.**	**Unit**	**Notes**
Optical Center Wavelength	λ_C	1575	1577	1580	nm	
Optical Spectrum Width (-20 dB)	$\Delta\lambda$	-	-	1	nm	
Side Mode Suppression Ratio	SMSR	30			dB	
Average Launch Optical Power	AOP	2		5	dBm	Launched into SMF
Power-OFF Transmitter Optical Power				-39	dBm	
Extinction Ratio	ER	6			dB	PRBS 2^31−1 at 10.3125
Transmitter Reflectance				-10	dB	
Transmitter and Dispersion Penalty	TDP			1.5	dB	Transmit on 20 km SMF
Optical Waveform Diagram	Compliant with IEEE Std 802.3av					Figure 1, margin >5%
10G EPON Transmitter Electrical Characteristics						
Data Input Differential Swing		120		850	mV	CML input, AC coupled
Input Differential Impedance		90	100	110	Ω	
Transmitter Disable Voltage - Low		0		0.8	V	


Transmitter Disable Voltage - High		2.0		V_{CC}	V	

1G EPON Transmitter Optical Characteristics						
Parameter	**Symbol**	**Min.**	**Typ.**	**Max.**	**Unit**	**Notes**
Optical Center Wavelength	λ_C	1480	1490	1500	nm	
Optical Spectrum Width (-20 dB)	$\Delta\lambda$			1	nm	
Side Mode Suppression Ratio	SMSR	30			dB	
Average Launch Optical Power	AOP	2		7	dBm	Launched into SMF
Power-OFF Transmitter Optical Power				-39	dBm	
Extinction Ratio	ER	9			dB	PRBS 2^7–1 test pattern at
Transmitter Reflectance				-10	dB	
Transmitter and Dispersion Penalty	TDP			2.3	dB	Transmit on 20 km SMF
Optical Waveform Diagram	Compliant with IEEE Std 802.3ah™-2004					Figure 2, margin >5%
1G EPON Transmitter Electrical Characteristics						
Data Input Differential Swing		200		1600	mV	LVPECL input, AC coupled
Input Differential Impedance		90	100	110	Ω	
Optical Return Loss Tolerance				15	dB	
Transmitter Disable Voltage - Low		0		0.8	V	
Transmitter Disable Voltage - High		2.0		V_{CC}	V	

Transmitter Eye Mask Definitions and Test Procedure

X1	X2	X3	Y1	Y2	Y3	Unit
0.25	0.40	0.45	0.25	0.28	0.40	UI

Figure 1: 10G EPON Transmitter Eye Mask Definitions



X1	X2	Y1	Y2	Y3	Unit
0.22	0.375	0.20	0.20	0.30	UI

Figure 2: 1G EPON Transmitter Eye Mask Definitions

10G EPON Receiver Optical Characteristics						
Parameter	**Symbol**	**Min.**	**Typ.**	**Max.**	**Unit**	**Notes**
Operating Wavelength		1260	1270	1280	nm	
Sensitivity	SEN			-28	dBm	PRBS 2^31−1 at 10.3125 Gbps BER <1×10^{-12} with
Saturation Optical Power	SAT	-6			dBm	
Loss Of Signal De-assert Level				-28	dBm	
Loss Of Signal Assert Level		-42			dBm	
Loss Of Signal Hysteresis		0.5		6	dB	
Receiver Reflectance				-12	dB	
10G EPON Receiver Electrical Characteristics						
Receiver Threshold Settling Time	$T_{SETTLING}$			800	ns	
Data Output Differential Swing		400		1600	mV	CML output, AC coupled
Loss Of Signal Assert Time			0.5		µs	
Loss Of Signal De-assert Time			0.5		µs	
Loss Of Signal Voltage - Low		0		0.4	V	
Loss Of Signal Voltage - High		2.4		VCC	V	

1G EPON Receiver Optical Characteristics						
Parameter	**Symbol**	**Min.**	**Typ.**	**Max.**	**Unit**	**Notes**
Operating Wavelength		1260		1360	nm	
Sensitivity	SEN			-29.78	dBm	PRBS 2^7−1 at 1.25 Gbps; BER
Saturation Optical Power	SAT	–9.38			dBm	
Loss Of Signal De-assert Level				-31	dBm	
Loss Of Signal Assert Level		-45			dBm	
Loss Of Signal Hysteresis		0.5		6	dB	
Receiver Reflectance				-12	dB	
1G EPON Receiver Electrical Characteristics						
Receiver Threshold Settling Time	$T_{SETTLING}$			400	ns	
Data Output Differential Swing		400		1600	mV	LVPECL output, DC coupled
Loss Of Signal Assert Time				512	ns	
Loss Of Signal Deassert Time				512	ns	
Loss Of Signal Voltage - Low		0		0.4	V	


Loss Of Signal Voltage - High		2.4		VCC	V	

Parameter	Unit	Min.	Typical	Max.
Bias Current_1G	mA	0		100
TX Power_1G	dBm	2		7
Bias Current_10G	mA	0		150
TX Power_10G	dBm	2		7
RX power monitor	dBm	-30		-6

Timing Sequences

Timing Sequence for RSSI

RSSI Characteristics						
Parameter	**Symbol**	**Min.**	**Typ.**	**Max.**	**Unit**	**Notes**
RSSI Trigger-Low		0		0.8	V	
RSSI Trigger-High		2.0		Vcc	V	
RSSI Trigger Delay	T_D	496	512	528	ns	
RSSI Trigger Width	T_W	584	600	616	ns	
I^2C Access Prohibited Time		500			μs	



Ordering Information

Product Name	Product Description
XFP-10G-EP-20	XFP 10G EPON OLT PR30, Tx 1577 nm/1490 nm, Rx 1270 nm/1310 nm, XFP form-factor SC/UPC, 20 km, 0 °C to +70 °C
XFP-10G-EP-20-I	XFP 10G EPON OLT PR30, Tx 1577 nm/1490 nm, Rx 1270 nm/1310 nm, XFP form-factor SC/UPC, 20 km, -40 to +85 °C

Contact Information

Ascent Communication Technology Ltd

AUSTRALIA
140 William Street, Melbourne
Victoria 3000, AUSTRALIA
Phone: +61-3-8691 2902

CHINA
Unit 1933, 600 Luban Road
200023, Shanghai CHINA
Phone: +86-21-60232616

EUROPE
Pfarrer-Bensheimer-Strasse 7a
55129 Mainz, GERMANY
Phone: +49 (0) 6136 926 3246

HONG KONG SAR
Unit 9, 12th Floor, Wing Tuck Commercial Centre
177 Wing Lok Street, Sheung Wan, HONG KONG
Phone: +852-2851 4722

USA
2710 Thomes Ave
Cheyenne, WY 82001, USA
Phone: +1-203 816 5188

VIETNAM
15 /F TTC Building, Duy Tan Street
Cau Giay Dist., Hanoi, VIETNAM
Phone: +84 168 481 8348

WEB: www.ascentcomtec.com

EMAIL: sales@ascentcomtec.com

Specifications and product availability are subject to change without notice.
Copyright © 2024 Ascent Communication Technology Limited. All rights reserved.
Ver. ACT_XFP-10G-EP-20_Datasheet_V1b_Aug_2024